

# Xeta9 TOPCON

## 900 MHz ISM

### Software Defined RTK Radio

---

The **Xeta9 Topcon** radio is an extremely capable and flexible industrial Single Channel Frequency Hopping Spread Spectrum (FHSS) software defined RTK radio covering the unlicensed 900 MHz frequency band that is an alternative drop-in replacement for the obsolete Topcon **RE-S1** radio.



The **Xeta9 Topcon** radio utilizes a XetaWave patented Dual Decode Digital Architecture™ that offers significant receiver performance. The **Xeta9 Topcon** radio can be used as a receiver, standalone repeater, or as an external radio for any Topcon base station.

## Key Features

---

**Compatibility** Over-the-air drop-in replacement for the Topcon RE-S1 radio.

**Interfaces** All the interfaces are physically and electrically the same as the Topcon RE-S1 radio.

**Role Types** User programmable to operate as a transmitter, receiver, or repeater.

**Adjustable RF Output** Power output up to 1 Watt (+30 dBm).

**Configuration** The radio can be configured using the Topcon Receiver Utility (TRU), the Modem TPS software, or its own built-in menus.

**Signaling Mode** Frequency hopping spread spectrum operations.

**Bands** 902 to 928 MHz ISM and adjustable to comply with various countries.

# Xeta9 Topcon Specifications

## Power

Transmit	275 mA @ +12 Vdc
Receive	90 mA @ +12 Vdc

## Environmental/Physical

Op. Temperature	-40°C to +75°C
Humidity	95% @ +40°C non-condensing
Dimensions	5.71" x 4.33" x 1.38"
Weight	400 grams

## Interfaces

Power	5-pin ODU   +7.5 to +14 Vdc
Data/Control	7-pin ODU   RS232
Control	7-pin ODU   RS232
RF	TNC & TNC-RP   50 Ohms

## Transmitter

## ISM FHSS

Frequency Range	902 to 928 MHz
Output Power	10 to 1000 mW (10 to 30 dBm)
Modulation	FSK
Rates (FH915)	9600, 12000, 17000, 24000, 51000
Rates (FH915 Ext)	3600, 4800, 6600, 9600, 19200
Channel Bandwidth	100 kHz
Frequency Stability	1.0 ppm

## Receiver

### Modulation

### Sensitivity

FSK	-97 dBm or better
-----	-------------------

## Functionality

Compatibility	Topcon RE-S1
Operating Modes	FH915, FH915 Ext
Roles	Transmitter, Receiver, Repeater
Error Correction	FEC(15.7), majority decoding
Channel	10, user selectable
Hopping Channels	128
Radio Link Rates	9600, 12000, 17000, 24000, 51000 bps, user selectable for FH915 3600, 4800, 6600, 9600, 19200 bps, user selectable for FH915 Ext
Serial Data Rates	600 to 921600 bps, user selectable
Configuration	Built-in menus, Topcon Receiver Utility Software, Modem TPS Software

## Ordering

XETA9-RE-S1	Enclosed, 2 Serial, Reverse Polarity TNC
XETA9-RE-S2	Enclosed, 2 Serial, Standard TNC



**XETAWAVE**  
CUSTOM RF SOLUTIONS

Specifications subject to change without notice.

2.2025